

Product Handling Information Sheet

SI GC 202 (Hgw 2572)

1. Company

Name/Address	Liedtke Kunststofftechnik Siemensstr. 32a, 42551 Velbert/Germany (DE) Phone +49 2051 605 105 info@liedtke-kunststofftechnik.de • www.liedtke-kunststofftechnik.de
--------------	---

2. Product Description

Product/Article	Technical semi-finished product (sheet / rod / moulded part)
Standard designation	SI GC 202 (EN 60893) / Hgw 2572 (DIN 7735)
Characterisation	Thermoset laminate (glass-fabric laminate, silicone resin)
Main constituents	• Silicone resin • Glass fabric
Constituents subject to labelling	none
Classification under REACH	Article
Notes	Not declared as a food-contact material.

3. Product Properties

Form/State	• solid (thermoset)
Colour	white
Odour	• nearly odourless
Density	1.7 g/cm ³
Glass transition temperature	– (thermoset, no melting point)
Limit temperature (continuous use)	180 °C
Thermal decomposition	chars/decomposes at very high temperature (does not melt)
Flammability	very high continuous-use temperature resistance, designed for high-temperature applications
Notes	Very high tracking resistance (CTI 600); designed for high-temperature electrical insulation.

4. Hazard Information

Special hazards to humans and the environment	none (in cured state)
Notes	Resin/glass fibre dust generated during machining should not be inhaled (mechanical skin irritation from glass fibres possible).

5. Handling and Storage

Handling	- The product can be machined with standard commercial machinery (sawing, milling, turning, drilling). - Prior to machining, the product should be at room temperature, or stored for at least 24 h in standard climate beforehand. - Ensure adequate dust extraction during machining (resin/glass fibre dust); use sharp, carbide-tipped or diamond-coated tools. - As a thermoset, cannot be reshaped or welded.
Storage recommendation	- horizontal - dry - protected from moisture - protected from direct UV/sunlight
Protective measures	Respiratory protection / extraction if dust is generated; avoid skin contact with machining dust
Shelf life	–
Notes	–

6. Transport

Transport	Not classified as dangerous goods under transport regulations.
Packaging	–
Notes	–

7. Fire-Fighting Measures

Suitable extinguishing media	- Water - Foam - Dry extinguishing agent - CO₂
Possible combustion products	- Carbon monoxide - Carbon dioxide - Silicon oxides
Required protective equipment	Firefighters and others exposed to combustion products should wear full protective clothing and self-contained breathing apparatus.
Notes	Collect fire residues and dispose of in accordance with local regulations.

8. Disposal Information

Recyclability	Thermoset (glass-fabric reinforced); material recycling only possible to a limited extent, consider thermal recycling.
EU waste catalogue	The product is not classified as hazardous under the European Waste Catalogue (EAK).
Disposal	The material may be sent to a suitable incineration plant in accordance with local regulations.
Waste code no.	• 07 02 13 - plastic waste • 17 02 03 - plastics (construction)
Notes	-

9. Labelling, Directives and Regulations

Labelling under EEC directives	not subject to labelling
Notes	-

10. REACH Information

Information	Under EC Directive 1907/2006/EC (REACH), Article 3, No. 3, our products are articles that are not subject to registration. The European Chemicals Regulation (EC) No. 1907/2006 (REACH), which entered into force on 1 June 2007, requires safety data sheets (SDS) only for hazardous substances and preparations. Our products are articles under REACH, so no SDS requirement applies.
-------------	---

11. Other Information

Other information	The above information is based on our current state of knowledge and does not constitute a guarantee of properties. Applicable laws and regulations must be observed by the recipient of our product on their own responsibility.
-------------------	---